

# PINTLE HITCH ADAPTER

This product can **ONLY** be used with the **Steel Weigh Safe Drop Hitch** in the **DROP** position.  
Cannot be used in the rise position.

## STEP 1



Ensure that you are using the **Weigh Safe Pintle Attachment (C)** with a **Steel Weigh Safe Drop Hitch**. Do not use with our aluminum drop hitch.

## STEP 2



Insert the **Weigh Safe Pintle Attachment (C)** into the **Steel Weigh Safe Slider (B)**. Ensure that the **Steel Weigh Safe Hitch Ball Pin (A)** is inserted fully into the **Slider**. **Do not operate without Steel Weigh Safe Hitch Ball Pin in place.**

## STEP 3



Place the **Steel Weigh Safe Slider** at the desired drop on the **Steel Draw Bar (D)** to ensure your vehicle and trailer are properly positioned. Draw bar **MUST** be used in the **DROP** position when using this pintle attachment.

## STEP 4



Insert the **Steel Dual Pin Key Lock Assembly (F)** into the **Slider** and lock in place by turning the key. **Pull** on the lock to ensure that it is engaged and place the **Dust Lock Cover (E)** over the lock. **Do not operate without making sure the lock is securely locked in place.**

# THANK YOU FOR CHOOSING WEIGH SAFE!


We hope you enjoy your adventures with your new hitch! If you have any issues or concerns regarding your product, we want to know about it.



Call/Text: 801.820.7020  
Email: support@weigh-safe.com

Why be **kinda safe**  
When you can be

**Weigh Safe**  



Scan QR for  
warranty/returns  
policies.



## IMPORTANT SAFETY INFORMATION

Ensure safety chains are attached between vehicle & trailer. **DO NOT** attach chains directly to hitch. Never exceed the **LOWER** rating between: A) tow vehicle manufacturer's load OR B) Weigh Safe Hitch GTW hitch ratings: 12,500 lbs (Pintle Attachment & 2" shank), 18,500 lbs (Pintle Attachment & 2.5" shank). Tongue weight should be between 10-15% of gross trailer weight. Weigh Safe Hitch max tongue weight is 1,500 lbs (2" shank) and 2,200 lbs (2.5" & 3" shanks). Secure your Weigh Safe Hitch to a standard 2", 2.5", or 3" receiver with locking pin. **DO NOT** use the Pintle Hitch Attachment in the rise position.